



## LEISTUNGSERKLÄRUNG



**DoP: 0122**

für fischer Bolzenanker FBZ, FBZ A4 (Metалldübel zur Verwendung im Beton (hoch belastbar)) – DE

1. Eindeutiger Kenncode des Produkttyps: **DoP: 0122**
2. Verwendungszweck(e): **Nachträgliche Befestigung im gerissenen und ungerissenen Beton, siehe Anhang, insbesondere Anhänge B 1 bis B 4**
3. Hersteller: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Straße 1, 72178 Waldachtal, Deutschland**
4. Bevollmächtigter: --
5. System(e) zur Bewertung und Überprüfung der Leistungsbeständigkeit: **1**
6. Europäisches Bewertungsdokument: **EAD 330232-00-0601**

Europäische Technische Bewertung: **ETA-17/0624; 2017-09-08**

Technische Bewertungsstelle: **DIBt**

Notifizierte Stelle(n): **1343 – MPA Darmstadt**

7. Erklärte Leistung(en):

### **Mechanische Festigkeit und Standsicherheit (BWR 1)**

- **Charakteristischer Widerstand für statische und quasi-statische Einwirkungen: Siehe Anhang, insbesondere Anhänge C 1 bis C 4**
- **Verschiebungen: Siehe Anhang, insbesondere Anhang C 5**

### **Brandschutz (BWR 2)**

- **Brandverhalten: Der Dübel erfüllt die Anforderungen der Klasse A 1**
- **Charakteristischer Widerstand unter Brandbeanspruchung: Siehe Anhang, insbesondere Anhang C 4**

8. Angemessene Technische Dokumentation und/oder Spezifische Technische Dokumentation: ---

Die Leistung des vorstehenden Produkts entspricht der erklärten Leistung/den erklärten Leistungen. Für die Erstellung der Leistungserklärung im Einklang mit der Verordnung (EU) Nr. 305/2011 ist allein der obengenannte Hersteller verantwortlich.

Unterzeichnet für den Hersteller und im Namen des Herstellers von:

Andreas Bucher, Dipl.-Ing.

Wolfgang Hengesbach, Dipl.-Ing., Dipl.-Wirtsch.-Ing.

*i.V. A. Bucher*

*i.V. W. Hengesbach*

Tumlingen, 2017-09-15

- Diese Leistungserklärung wurde in verschiedenen Sprachversionen erstellt. Für den Fall unterschiedlicher Auslegung hat immer die englische Version Vorrang.
- Der Anhang enthält freiwillige und ergänzende Informationen in englischer Sprache. Diese gehen über die (sprachneutral angegebenen) gesetzlichen Anforderungen hinaus.

**Specific Part****1 Technical description of the product**

The fischer Bolt Anchor FBZ is an anchor made of galvanised steel (FBZ) or made of stainless steel (FBZ A4) which is placed into a drilled hole and anchored by torque-controlled expansion. The product description is given in Annex A.

**2 Specification of the intended use in accordance with the applicable European Assessment Document**

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

**3 Performance of the product and references to the methods used for its assessment****3.1 Mechanical resistance and stability (BWR 1)**

Essential characteristic	Performance
Characteristic resistance for static and quasi static action	See Annex C 1 to C 4
Displacements	See Annex C 5

**3.2 Safety in case of fire (BWR 2)**

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Characteristic resistance under fire exposure	See Annex C 4


**4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base**

In accordance with the European Assessment Document EAD Nr. 330232-00-0601 the applicable European legal act is: [96/582/EC].



The system to be applied is: 1




Cone bolt manufactured by cold - forming:



Cone bolt manufactured by turning:



- ① Expansion sleeve
- ② Cone bolt (cold – formed or turned)
- ③ Washer
- ④ Hexagon nut




(Fig. not to scaled)

fischer Bolt Anchor FBZ, FBZ A4

**Product description**  
Installed condition

**Annex A 1**

**Product marking and letter-code:**



Product marking, example:



Brand | type of fastener placed at marking area 2 or marking area 3

Thread size / max. thickness of the fixture ( $t_{fix}$ ) identification A4 placed at marking area 2

FBZ: carbon steel, galvanized  
 FBZ A4: stainless steel

**Table A2.1:** Letter - code at marking area 1:

Marking	(a)	(b)	(c)	(d)	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(K)
Max. $t_{fix}$	5	10	15	20	5	10	15	20	25	30	35	40	45	50
$B \geq$ [mm]	M8	40	45	-	50	55	60	65	70	75	80	85	90	95
	M10	45	50	55	60	65	70	75	80	85	90	95	100	105
	M12	55	60	65	70	75	80	85	90	95	100	105	110	115
	M16	70	75	80	85	90	95	100	105	110	115	120	125	130
	M20	-	-	-	-	105	110	115	120	125	130	135	140	145

Marking	(L)	(M)	(N)	(O)	(P)	(R)	(S)	(T)	(U)	(V)	(W)	(X)	(Y)	(Z)
Max. $t_{fix}$	60	70	80	90	100	120	140	160	180	200	250	300	350	400
$B \geq$ [mm]	M8	105	115	125	135	145	165	185	205	225	245	295	345	395
	M10	120	130	140	150	160	180	200	220	240	260	310	360	410
	M12	130	140	150	160	170	190	210	230	250	270	320	370	420
	M16	145	155	165	175	185	205	225	245	265	285	335	385	435
	M20	160	170	180	190	200	220	240	260	280	300	350	400	450

**Calculation existing  $h_{ef}$  for installed fasteners:**

$$\text{existing } h_{ef} = B_{(\text{according to table A2.1})} - \text{existing } t_{fix}$$

Thickness of the fixture  $t_{fix}$  including thickness of fastener plate  $t$  and e.g. thickness of grout layer  $t_{grout}$  or other non-structural layers


(Fig. not to scaled)

fischer Bolt Anchor FBZ, FBZ A4

**Product description**  
 Product marking and letter code

**Annex A 2**

**Product dimensions**



**Table A3.1:** Dimensions [mm]

Part	Designation		FBZ, FBZ A4				
			M8	M10	M12	M16	M20
1	Expansion sleeve	Sheet thickness	1,3	1,4	1,6	2,4	
2	Cone bolt	Thread size M	8	10	12	16	20
		$L_G$	19	26	31	40	50
3	Washer	$t_s$	1,4	1,8	2,3	2,7	
		$\varnothing d_s$	15	19	23	29	36
4	Hexagon nut	Wrench size	13	17	19	24	30

(Fig. not to scaled)

fischer Bolt Anchor FBZ, FBZ A4

**Product description**  
Dimensions


**Annex A 3**

<b>Specifications of intended use</b>					
<b>Anchorage subject to:</b>					
Size	<b>FBZ, FBZ A4</b>				
	<b>M8</b>	<b>M10</b>	<b>M12</b>	<b>M16</b>	<b>M20</b>
Static and quasi-static loads	✓				
Cracked and uncracked concrete					
Fire exposure					
<p><b>Base materials:</b></p> <ul style="list-style-type: none"> <li>Reinforced and unreinforced normal weight concrete (cracked and uncracked) according to EN 206-1: 2000</li> <li>Strength classes C20/25 to C50/60 according to EN 206-1: 2000</li> </ul> <p><b>Use conditions (Environmental conditions):</b></p> <ul style="list-style-type: none"> <li>Structures subject to dry internal conditions (FBZ, FBZ A4)</li> <li>Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently damp internal condition, if no particular aggressive conditions exist (FBZ A4)</li> </ul> <p>Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used)</p> <p><b>Design:</b></p> <ul style="list-style-type: none"> <li>Anchorage are to be designed under the responsibility of an engineer experienced in anchorages and concrete work</li> <li>Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.)</li> <li>Design of fastenings according to FprEN 1992-4: 2016 and EOTA Technical Report TR 055</li> <li>For effective embedment depth <math>h_{ef} &lt; 40</math> mm and <math>h_{min} \geq 80</math> mm and / or <math>&lt; 100</math> mm only statically indeterminate fixings (e.g. lightweight suspended ceilings with internal exposure) are covered by the ETA</li> </ul>					
fischer Bolt Anchor FBZ, FBZ A4					<b>Annex B 1</b>
<b>Intended use</b> Specifications					



**Table B2.1:** Installation parameters

Size	FBZ, FBZ A4				
	M8	M10	M12	M16	M20
Nominal drill hole diameter $d_0 =$	8	10	12	16	20
Maximum bit diameter with hammer or hollow drilling $d_{cut,max}$ [mm]	8,45	10,45	12,5	16,5	20,55
Maximum bit diameter with diamond drilling	8,15		12,25	16,45	20,50
Overall fastener embedment depth in the concrete $h_{nom} \geq$ (L) [mm]	44,5 (9,5)	52,0 (12)	63,5 (13,5)	82,5 (17,5)	120 (20)
Depth of drill hole to deepest point $h_1 \geq$	Existing $h_{ef} + L = h_{nom}$ $h_{nom} + 5$				$h_{nom} + 10$
Diameter of clearance hole in the fixture $d_f \leq$ [mm]	9	12	14	18	22
Required setting torque $T_{inst} =$ [Nm]	20	45	60	110	200



- $h_{ef}$  = Effective embedment depth
- $t_{fix}$  = Thickness of the fixture
- $h_1$  = Depth of drill hole to deepest point
- $h$  = Thickness of the concrete member
- $h_{min}$  = Minimum thickness of concrete member
- $h_{nom}$  = Overall fastener embedment depth in the concrete
- $T_{inst}$  = Required setting torque

(Fig. not to scaled)

fischer Bolt Anchor FBZ, FBZ A4

**Intended use**  
Installation parameters

**Annex B 2**



**Table B3.1:** Minimum thickness of concrete members, minimum spacings and minimum edge distances of anchors for **standard anchorage depth ( $h_{ef, sta}$ )**

Size		FBZ, FBZ A4				
		M8	M10	M12	M16	M20
<b>Standard anchorage depth</b> $h_{ef, sta} \geq$		<b>45</b>	<b>60</b>	<b>70</b>	<b>85</b>	<b>100</b>
Concrete members with thickness $\geq 2 \times h_{ef, sta}$	Minimum thickness of concrete member $h_{min, 1}$ [mm]	<b>100</b>	<b>120</b>	<b>140</b>	<b>170</b>	<b>200</b>
	<b>Uncracked concrete</b>					
	Minimum spacing $\frac{s_{min}}{\text{for } c \geq}$ [mm]	40		50	65	95
		50	60	70	95	180
	Minimum edge distance $\frac{c_{min}}{\text{for } s \geq}$	40	45	55	65	95
		100	80	110	150	190
	<b>Cracked concrete</b>					
	Minimum spacing $\frac{s_{min}}{\text{for } c \geq}$ [mm]	35	40	50	65	95
50		55	70	95	140	
Minimum edge distance $\frac{c_{min}}{\text{for } s \geq}$	40	45	55	65	85	
	70	80	110	150	190	
Concrete members with thickness $< 2 \times h_{ef, sta}$	Minimum thickness of concrete member $h_{min, 2}$ [mm]	<b>80</b>	<b>100</b>	<b>120</b>	<b>140</b>	<b>160</b>
	<b>Cracked and uncracked concrete</b>					
	Minimum spacing $\frac{s_{min}}{\text{for } c \geq}$ [mm]	35	40	50	80	125
		70	100	90	130	220
	Minimum edge distance $\frac{c_{min}}{\text{for } s \geq}$	40	60		65	125
100		90	120	180	230	

Intermediate values for  $s_{min}$  and  $c_{min}$  inside of the same thickness of concrete member by linear interpolation**Table B3.2:** Minimum thickness of concrete members, minimum spacings and minimum edge distances of anchors for **reduced anchorage depth ( $h_{ef, red}$ )**

Size		FBZ, FBZ A4				
		M8	M10	M12	M16	
<b>Reduced anchorage depth</b> $h_{ef, red} \geq$		<b>35<sup>1)</sup></b>	<b>40</b>	<b>50</b>	<b>65</b>	
Concrete members with thickness $\geq 2 \times h_{ef, red}$	Minimum thickness of concrete member $h_{min, 3}$ [mm]	<b>80</b>		<b>100</b>	<b>140</b>	
	<b>Uncracked concrete</b>					
	Minimum spacing $\frac{s_{min}}{\text{for } c \geq}$ [mm]	40		50	65	
		100	110		130	
	Minimum edge distance $\frac{c_{min}}{\text{for } s \geq}$	45	55		65	
		180	220		250	
	<b>Cracked concrete</b>					
	Minimum spacing $\frac{s_{min}}{\text{for } c \geq}$ [mm]	40		50	65	
90		110		130		
Minimum edge distance $\frac{c_{min}}{\text{for } s \geq}$	45	55		65		
	180	220		250		

Intermediate values for  $s_{min}$  and  $c_{min}$  by linear interpolation<sup>1)</sup> Only in anchoring structural components which are statically indeterminate

fischer Bolt Anchor FBZ, FBZ A4

**Intended use**  
Minimum thickness of member, minimum spacings and edge distances









**Annex B 3**

**Installation instructions:**


- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Use of the anchor only as supplied by the manufacturer without exchanging the components of the anchor
- Checking before placing the anchor to ensure that the strength class of the concrete in which the anchor is to be placed is in the range given and is not lower than that of the concrete to which the characteristic loads apply
- Check of concrete being well compacted, e.g. without significant voids
- Hammer, hollow or diamond drilling according to Annex B4
- Drill hole created perpendicular +/- 5° to concrete surface, positioning without damaging the reinforcement
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application
- It must be ensured that in case of fire local spalling of the concrete cover does not occur

**Installation instructions: Drilling and cleaning the hole**


Types of drills and cleaning

<p>Hammer drill</p>		 <p>1: Drill the hole</p>	 <p>2: Clean the hole</p>
<p>Hollow drill</p>		 <p>1: Drill the hole with automatic cleaning</p>	<p>-</p>
<p>Diamond drill</p>		 <p>1: Drill the hole</p>	 <p>2: Clean the hole</p>


**Installation instructions: Installation of the anchor**



3: Set the fastener



4: Apply  $T_{inst}$



5: Installed fastener

fischer Bolt Anchor FBZ, FBZ A4

**Intended use**  
Installation instructions

**Annex B 4**

<b>Table C1.1: Characteristic values of tension resistance for standard anchorage depth</b>								
Size	FBZ, FBZ A4							
	M8	M10	M12	M16	M20			
<b>Steel failure for standard anchorage depth</b>								
Characteristic resistance	FBZ	$N_{Rk,s}$	[kN]	16,6	28,3	43,2	67,0	123,3
	FBZ A4	$N_{Rk,s}$	[kN]	17,0	29,0	44,3	70,6	124,9
Partial factor for steel failure		$\gamma_{Ms}$ <sup>3)</sup>	[-]	1,5				
<b>Pullout failure for standard anchorage depth</b>								
Effective anchorage depth for calculation	$h_{ef,sta} \geq$	[mm]		45	60	70	85	100
Characteristic resistance in cracked concrete C20/25		$N_{Rk,p}$	[kN]	6	10	16	26	30
Characteristic resistance in uncracked concrete C20/25		$N_{Rk,p}$	[kN]	11	16	17	34	42
Increasing factors for $N_{Rk,p}$ for cracked and uncracked concrete		C25/30		1,12				
		C30/37		1,22				
		C35/45		1,32				
		$\psi_c$ C40/50		1,41				
		C45/55		1,50				
	C50/60		1,58					
Installation sensitivity factor		$\gamma_{inst}$	[-]	1,0				
<b>Concrete cone and splitting failure for standard anchorage depth in applications with concrete members of thickness <math>\geq 2x h_{ef,sta}</math></b>								
Effective anchorage depth	$h_{ef}$	[mm]		45	60	70	85	100
Factor for uncracked concrete	$k_1 = k_{ucr,N}$	[-]		11,0 <sup>2)</sup>				
Factor for cracked concrete	$k_1 = k_{cr,N}$	[-]		7,7 <sup>2)</sup>				
Minimum thickness of concrete member	$h_{min,1}$	[mm]		100	120	140	170	200
Characteristic spacing	$s_{cr,N}$	[mm]		3 $h_{ef}$				
Characteristic edge distance	$c_{cr,N}$	[mm]		1,5 $h_{ef}$				
Spacing (splitting failure) <sup>1)</sup>	$s_{cr,sp}$	[mm]		140	180	210	260	370
Edge distance (splitting failure) <sup>1)</sup>	$c_{cr,sp}$	[mm]		70	90	105	130	185
<b>Concrete cone and splitting failure for standard anchorage depth in applications with concrete members of thickness <math>&lt; 2x h_{ef,sta}</math></b>								
Effective anchorage depth	$h_{ef}$	[mm]		45	60	70	85	100
Factor for uncracked concrete	$k_1 = k_{ucr,N}$	[-]		11,0 <sup>2)</sup>				
Factor for cracked concrete	$k_1 = k_{cr,N}$	[-]		7,7 <sup>2)</sup>				
Minimum thickness of concrete member	$h_{min,2}$	[mm]		80	100	120	140	160
Characteristic spacing	$s_{cr,N}$	[mm]		3 $h_{ef}$				
Characteristic edge distance	$c_{cr,N}$	[mm]		1,5 $h_{ef}$				
Spacing (splitting failure) <sup>1)</sup>	$s_{cr,sp}$	[mm]		180	240	280	340	480
Edge distance (splitting failure) <sup>1)</sup>	$c_{cr,sp}$	[mm]		90	120	140	170	240
<sup>1)</sup> Intermediate values for $s_{cr,sp}$ and $c_{cr,sp}$ between concrete thickness $h_{min,2}$ and $h_{min,1}$ by linear interpolation <sup>2)</sup> Based on concrete strength as cylinder strength <sup>3)</sup> In absence of other national regulations								
fischer Bolt Anchor FBZ, FBZ A4							<b>Annex C 1</b>	
<b>Performances</b> Characteristic values of resistance under tension loads								

<b>Table C2.1: Characteristic values of tension resistance for reduced anchorage depth</b>							
Size	FBZ, FBZ A4						
	M8	M10	M12	M16			
<b>Steel failure for reduced anchorage depth</b>							
Characteristic resistance	FBZ	$N_{Rk,s}$	[kN]	16,6	28,3	43,2	67,0
	FBZ A4	$N_{Rk,s}$	[kN]	17,0	29,0	44,3	70,6
Partial factor for steel failure		$\gamma_{Ms}$ <sup>3)</sup>	[-]	1,5			
<b>Pullout failure for reduced anchorage depth</b>							
Effective anchorage depth for calculation	$h_{ef,red} \geq$	[mm]		35 <sup>1)</sup>	40	50	65
Characteristic resistance in cracked concrete C20/25		$N_{Rk,p}$	[kN]	4	7	10	15
Characteristic resistance in uncracked concrete 20/25		$N_{Rk,p}$	[kN]	8	10	15	22
Increasing factors for $N_{Rk,p}$ for cracked and uncracked concrete		C25/30		1,12			
		C30/37		1,22			
		C35/45		1,32			
		C40/50	$\psi_c$	1,41			
		C45/55		1,50			
		C50/60		1,58			
Installation sensitivity factor		$\gamma_{inst}$	[-]	1,0			
<b>Concrete cone and splitting failure for reduced anchorage depth</b>							
Effective anchorage depth	$h_{ef}$	[mm]		35 <sup>1)</sup>	40	50	65
Factor for uncracked concrete	$k_1 = k_{ucr,N}$	[-]		11 <sup>2)</sup>			
Factor for cracked concrete	$k_1 = k_{cr,N}$	[-]		7,7 <sup>2)</sup>			
Min. thickness of concrete member	$h_{min,3}$			80		100	140
Characteristic spacing	$s_{cr,N}$			3 $h_{ef}$			
Characteristic edge distance	$c_{cr,N}$	[mm]		1,5 $h_{ef}$			
Spacing (splitting failure)	$s_{cr,sp}$			140	160	200	260
Edge distance (splitting failure)	$c_{cr,sp}$			70	80	100	130
<sup>1)</sup> Use restricted to anchoring of structural components which are statically indeterminate <sup>2)</sup> Based on concrete strength as cylinder strength <sup>3)</sup> In absence of other national regulations							
fischer Bolt Anchor FBZ, FBZ A4							<b>Annex C 2</b>
<b>Performances</b> Characteristic values of resistance under tension loads							



<b>Table C3.1: Characteristic values of shear resistance for standard and reduced anchorage depth</b>								
Size			FBZ, FBZ A4					
			M8	M10	M12	M16	M20	
<b>Steel failure without lever arm for standard and reduced anchorage depth</b>								
Characteristic resistance	FBZ	$V_{Rk,s}$	[kN]	12,0	21,4	30,6	55,0	70,0
	FBZ A4	$V_{Rk,s}$		16,1	26,5	37,4	57,2	
Partial factor for steel failure		$\gamma_{Ms}^{1)}$	[-]	1,25				
Factor for ductility		$k_7$		1,0				
<b>Standard anchorage depth</b>								
<b>Steel failure with lever arm</b>								
Characteristic bending resistance	FBZ	$M_{Rk,s}^0$	[Nm]	26	52	92	233	513
	FBZ A4	$M_{Rk,s}^0$		29	59	100	256	519
Partial factor for steel failure		$\gamma_{Ms}^{1)}$	[-]	1,25				
Factor for ductility		$k_7$		1,0				
<b>Concrete pryout failure</b>								
Factor for pryout failure		$k_8$	[-]	2,8	3,2		3,0	2,6
<b>Concrete edge failure</b>								
Effective embedment depth for calculation		$l_f$	[mm]	45	60	70	85	100
Outside diameter of a fastener		$d_{nom}$		8	10	12	16	20
Installation sensitivity factor		$\gamma_{inst}^{1)}$	[-]	1,0				
<b>Reduced anchorage depth</b>								
<b>Steel failure with lever arm</b>								
Characteristic bending resistance	FBZ	$M_{Rk,s}^0$	[Nm]	20	44	92	184	-
	FBZ A4	$M_{Rk,s}^0$		21	45	100	193	-
Partial factor for steel failure		$\gamma_{Ms}^{1)}$	[-]	1,25				
Factor for ductility		$k_2$		1,0				
<b>Concrete pryout failure</b>								
Factor for pryout failure		$k_8$	[-]	2,5	2,6	3,1	3,2	-
<b>Concrete edge failure</b>								
Effective embedment depth for calculation		$l_f$	[mm]	35	40	50	65	-
Outside diameter of a fastener		$d_{nom}$		8	10	12	16	-
1) In absence of other national regulations								
fischer Bolt Anchor FBZ, FBZ A4							<b>Annex C 3</b>	
<b>Performances</b> Characteristic values of resistance under shear loads								

**Table C4.1:** Characteristic values of **tension** resistance under **fire exposure**

Size		FBZ, FBZ A4					
		M8	M10	M12	M16	M20	
$h_{ef} \geq$ [mm]		35 / 45	40 / 60	50 / 70	65 / 85	100	
Characteristic resistance <b>steel failure</b>	$N_{Rk,s,fi}$	R30	1,4	2,8	5,0	9,4	14,7
		R60	1,2	2,3	4,1	7,7	12,0
		R90	0,9	1,9	3,2	6,0	9,4
		R120	0,8	1,6	2,8	5,2	8,1
Characteristic resistance <b>Concrete cone failure</b>	$N_{Rk,c,fi}$	R30 - R90	$7,7 \cdot h_{ef}^{1,5} \cdot (20)^{0,5} \cdot h_{ef} / 200 / 1000$				
		R120	$7,7 \cdot h_{ef}^{1,5} \cdot (20)^{0,5} \cdot h_{ef} / 200 / 1000 \cdot 0,8$				
		[kN]					
Characteristic resistance <b>pullout failure</b>	$N_{Rk,p,fi}$	R30	0,9 / 2,0	2,2 / 3,3	3,0 / 5,0	4,5 / 6,8	8,6
		R60	0,8 / 2,0				
		R90	0,5 / 2,0	1,7 / 2,6	2,4 / 4,0	3,6 / 5,4	6,9
		R120	0,3 / 1,6				

**Table C4.2:** Characteristic values of **shear** resistance under **fire exposure**

Size FBZ, FBZ A4			R30		R60	
			$V_{Rk,s,fi,30}$ [kN]	$M^0_{Rk,s,fi,30}$ [Nm]	$V_{Rk,s,fi,60}$ [kN]	$M^0_{Rk,s,fi,60}$ [Nm]
M8	$h_{ef} \geq$	35	1,8	1,4	1,6	1,2
M10		40	3,6		2,9	3,0
M12		50	6,3	7,8	4,9	6,4
M16		65	11,7	19,9	9,1	16,3
M20		100	18,2	39,0	14,2	31,8
Size FBZ, FBZ A4			R90		R120	
			$V_{Rk,s,fi,90}$ [kN]	$M^0_{Rk,s,fi,90}$ [Nm]	$V_{Rk,s,fi,120}$ [kN]	$M^0_{Rk,s,fi,120}$ [Nm]
M8	$h_{ef} \geq$	35	1,3	1,0	1,2	0,8
M10		40	2,2	2,4	1,9	2,1
M12		50	3,5	5,0	2,8	4,3
M16		65	6,6	12,6	5,3	11,0
M20		100	10,3	24,6	8,3	21,4

**Table C4.3:** Minimum spacings and minimum edge distances of anchors under **fire exposure** for **tension** and **shear** load

Size		FBZ, FBZ A4				
		M8	M10	M12	M16	M20
Spacing	$s_{min}$	Annex B3				
Edge distance	$c_{min}$	$c_{min} = 2 \cdot h_{ef}$ for fire exposure from more than one side $c_{min} \geq 300$ mm				

fischer Bolt Anchor FBZ, FBZ A4

**Performances**  
Characteristic values of resistance under fire exposure

**Annex C 4**

**Table C5.1:** Displacements under static and quasi static **tension** loads

Size	FBZ, FBZ A4				
	M8	M10	M12	M16	M20
<b>Displacement – factor for tensile load<sup>1)</sup></b>					
$\delta_{N0}$ - factor in cracked concrete	0,22	0,12	0,09	0,08	0,07
$\delta_{N\infty}$ - factor [mm/kN]	0,78	0,40	0,19	0,09	
$\delta_{N0}$ - factor in uncracked concrete	0,07	0,05	0,06		0,05
$\delta_{N\infty}$ - factor	0,29	0,21	0,14	0,10	0,06

**Table C5.2:** Displacements under static and quasi static **shear** loads

Size	FBZ				
	M8	M10	M12	M16	M20
<b>Displacement – factor for shear load<sup>2)</sup></b>					
$\delta_{V0}$ - factor in cracked concrete	0,35	0,37	0,27	0,10	0,09
$\delta_{V\infty}$ - factor [mm/kN]	0,52	0,55	0,40	0,14	0,15
<b>FBZ A4</b>					
$\delta_{V0}$ - factor in uncracked concrete	0,23	0,19	0,18	0,10	0,11
$\delta_{V\infty}$ - factor [mm/kN]	0,27	0,22	0,16	0,11	0,05

<sup>1)</sup> Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0} - \text{factor} \cdot N_{ED}$$

$$\delta_{N\infty} = \delta_{N\infty} - \text{factor} \cdot N_{ED}$$

( $N_{ED}$ : Design value of the applied tension force)

<sup>2)</sup> Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0} - \text{factor} \cdot V_{ED}$$

$$\delta_{V\infty} = \delta_{V\infty} - \text{factor} \cdot V_{ED}$$

( $V_{ED}$ : Design value of the applied shear force)

fischer Bolt Anchor FBZ, FBZ A4

**Performances**  
Displacements under tension and shear loads

**Annex C 5**