


Artikelnummer/Itemnumber: 4272UZH

Edelstahlpfosten Ø 76 mm mit Ziernut, umlegbar, selbsteinrastende Verriegelung zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Profilzylinderschloss und drei Schlüsseln, ohne



Stainless steel post Ø 76 mm with decorative ring, foldable, self-engaging lock for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with Euro profile cylinder lock and three keys, without eyelet



Artikelbeschreibung:

Edelstahlpfosten Ø 76 mm Überflur ca. 900 mm, umlegbar, selbsteinrastende Verriegelung zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Profilzylinderschloss und drei Schlüsseln, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 9,00 kg/St
Material:
Edelstahl

item description:

Stainless steel post Ø 76 mm with decorative ring, foldable, self-engaging lock for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with Euro profile cylinder lock and three keys, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 9,00 kg/pc
material:
stainless steel