


Artikelnummer/Itemnumber: 460HB/1

Absperrpfosten Stahlrohr Ø 60 x 2,5 mm herausnehmbar ohne Verschluss, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, mit 1 Öse

Barrier posts Steel tube Ø 60 x 2,5 mm removable without locking mechanism, hot-dip galvanized and white coated with three red reflecting stripes, with 1 eyelet



Artikelbeschreibung:

Absperrpfosten Stahlrohr Ø 60 x 2,5 mm mit aufgeschweißter Stahlkappe 900 mm Überflur herausnehmbar, ohne Verschluss mit Bodenhülse Typ 460.10 ca. 400 mm Unterflur, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, mit 1 Öse

Verwendungszweck:

Absperrpfosten zur Sperrung von Gehwegen für Fahrzeuge, zur Abgrenzung von Wegen.

Technische Daten:

Gewicht: 7,00 kg/St
Material:
STahl S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Barrier posts Steel tube Ø 60 x 2.5 mm with welded steel cap 900 mm above ground removable, without locking mechanism with ground socket part-no. 460.10 approx. 400 mm below ground, hot-dip galvanized and white coated with three red reflecting stripes, with 1 eyelet

designated purpose:

Barrier posts for closing off sidewalks for vehicles, for demarcating paths.

technical specifications:

weight: 7,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated