


## Artikelnummer/Itemnumber: 464UZZ

Absperr-Stilpfosten Serie 464B Ø 60 mm, umlegbar, selbsteinrastende Verriegelung für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, mit Profilzylinderschloss und drei Schlüsseln, ohne Öse

Ornamental bollard Series 464B Ø 60 mm, foldable, self-engaging lock to be fixed by plugs, with base plate 100 x 150 mm, with Euro profile cylinder lock and three keys, without eyelet



### Artikelbeschreibung:

Absperr-Stilpfosten mit Ziernut aus Stahlrundrohr Ø 60 mm, ca. 950 mm Überflur, feuerverzinkt und anthrazitgrau DB 703 beschichtet., umlegbar, selbsteinrastende Verriegelung für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, mit Profilzylinderschloss und drei Schlüsseln, ohne Öse

### Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

### Technische Daten:

Gewicht: 7,00 kg/St  
Material:  
S235 JR

Oberfläche:  
Feuerverzinkt und Pulverbeschichtet

### item description:

The ornamental bollard series Ø 60 mm A light-weight but very stylish version of our ornamental bollards. Barrier ornamental bollard of round steel tube Ø 60 mm, approx. 950 mm above ground, hot-dip galvanized and coated anthracite grey (RAL 7016)., foldable, self-engaging lock to be fixed by plugs, with base plate 100 x 150 mm, with Euro profile cylinder lock and three keys, without eyelet

### designated purpose:

For stopping, and securing or saving of areas.

### technical specifications:

weight: 7,00 kg/pc  
material:  
S235 JR

surface:  
hot dipped galvanized and powder coated