


Artikelnummer/Itemnumber: 476/1

Absperrpfosten Stahlrohr Ø 76 x 2,6 mm
ortsfest, zum Einbetonieren feuerverzinkt /
weiß beschichtet, feuerverzinkt, mit 1 Öse

Barrier posts Steel tube Ø 76 x 2,6 mm
stationary, for casting in concrete hot-dip
galvanized / white coated, hot-dip galvanized,
with 1 eyelet



Artikelbeschreibung:

Absperrpfosten Stahlrohr Ø 76 x 2,6 mm mit
aufgeschweißter Stahlkappe 900 mm Überflur
ortsfest, zum Einbetonieren mit Erdanker
Gesamtlänge: 1400 mm, feuerverzinkt, mit 1
Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von
Bereichen.

Technische Daten:

Gewicht: 7,00 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkung nach DIN ISO 1461

item description:

Barrier post steel tube Ø 76 x 2.6 mm with
welded steel cap 900 mm above ground
stationary, for casting in concrete with ground
anchor total length: 1400 mm, hot-dip
galvanized, with 1 eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 7,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized acc. to DIN ISO 1461