


Artikelnummer/Itemnumber: 476FUB

Absperrpfosten Stahlrohr \varnothing 76 x 2,6 mm umlegbar, mit Dreikantverschluss, für Dübelbefestigung mit Bodenplatte 100 x 150 mm, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, ohne

Barrier posts Steel tube \varnothing 76 x 2,6 mm foldable, with triangular locking mechanism, to be fixed by plugs with base plate 100 x 150 mm, hot-dip galvanized and white coated with three red reflecting stripes, without eyelet



Artikelbeschreibung:

Absperrpfosten Stahlrohr \varnothing 76 x 2,6 mm mit aufgeschweißter Stahlkappe 900 mm Überflur umlegbar, mit Dreikantverschluss nach DIN 3223, selbsteinrastende Verriegelung, für Dübelbefestigung mit Bodenplatte 100 x 150 mm, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 7,00 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Barrier post steel tube \varnothing 76 x 2.6 mm with welded steel cap 900 mm above ground foldable, with triangular locking mechanism acc. with DIN 3223, self-engaging lock, to be fixed by plugs with base plate 100 x 150 mm, hot-dip galvanized and white coated with three red reflecting stripes, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 7,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated