

## Artikelnummer/Itemnumber: 482UZHB

Absperr-Stilpfosten Serie 482B Ø 82 mm, umlegbar, selbsteinrastende Verriegelung zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Profilzylinderschloss und drei Schlüsseln, ohne

Ornamental bollard Series 482B Ø 82 mm, foldable, self-engaging lock for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with Euro profile cylinder lock and three keys without eyelet



## Artikelbeschreibung:

Stilpoller aus Stahlrundrohr Ø 82 mm ca. 900 mm Überflur, feuerverzinkt und beschichtet, Farbe: DB703, umlegbar, selbsteinrastende Verriegelung zum Einbetonieren, mit feuerverzinkter Bodenhülse Typ 470.60, ca. 400 mm Unterflur, mit Profilzylinderschloss und drei Schlüsseln, ohne Öse

## item description:

Ornamental bollard of round steel tube Ø 82 mm approx. 900 mm above ground, hot-dip galvanized and coated, color: DB703, foldable, self-engaging lock for casting in concrete, with hot-dip galvanized ground socket part-no. 470.60, approx. 400 mm below ground, with Euro profile cylinder lock and three keys, without eyelet

## Technische Daten:

Gewicht: 13,00 kg/St  
Material:  
S235 JR

Oberfläche:  
Feuerverzinkt und Pulverbeschichtet

## technical specifications:

weight: 13,00 kg/pc  
material:  
S235 JR

surface:  
hot dipped galvanized and powder coated