


Artikelnummer/Itemnumber: 485FUB

Absperr-Stilpfosten Serie 485B Ø 82 mm, umlegbar, selbsteinrastende Verriegelung für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, mit Dreikantverschluss nach DIN 3223, ohne Öse

Ornamental bollard Series 485B Ø 82 mm, foldable, self-engaging lock to be fixed by plugs, with base plate 100 x 150 mm, with triangular locking mechanism acc. with DIN 3223, without eyelet



Artikelbeschreibung:

Stilpoller aus Stahlrundrohr Ø 82 mm ca. 900 mm Überflur, feuerverzinkt und beschichtet, Farbe: RAL 9005 matt (mattschwarz), umlegbar, selbsteinrastende Verriegelung für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, mit Dreikantverschluss nach DIN 3223, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 10,50 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Ornamental bollard of round steel tube Ø 82 mm approx. 900 mm above ground, hot-dip galvanized and coated, color: RAL 9005 matt (jet black), foldable, self-engaging lock to be fixed by plugs, with base plate 100 x 150 mm, with triangular locking mechanism acc. with DIN 3223, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 10,50 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated